

# Acrylic Foam Tape

## 3040

### PRODUCT DESCRIPTION

3040 Acrylic Foam Tape is white, double-coated acrylic foam tape used in a variety of automotive applications. Considering of high performance acrylic adhesive and liner. Designed to have an excellent long term holding power.

### APPLICATIONS

- \* Interior and exterior industrial applications
- \* Attachment emblems for the electronic application.
- \* Attachment advertising materials.
- \* Transportation bonding application:  
Roof bows, FRP panels, interior panel stiffeners, Side rail bonding, etc



### PHYSICAL PROPERTIES

Foam	White acrylic
Adhesive	Acrylic Adhesive
Liner	Low Density Red PE film
Thickness	0.64mm(0.025 in)

### TECHNICAL PERFORMANCE

Peel adhesion	950 g/cm	
Holding power	0.5mm	23°C/min / 25mm*25mm*kg
Heat resistance	over 120°C	
Shear strength	6.5 kg/cm <sup>2</sup>	
Tensile strength	0.6 kg/cm	
Elongation	750 %	
Density	800 kg/m <sup>3</sup>	

### WIDTH & LENGTH OF ROLL

Roll width	Roll Length
min 8mm	33 meters(36 yards)
max 800mm	66 meters(72 yards)

### STORAGE DETAILS and SELF LIFE

One year from date of despatch when stored at 22°C(72°F) and 50% relative humidity. Shelf life can vary with temperature and humidity.

[www.plustape.com](http://www.plustape.com)