

Acrylic Foam Tape

3050

PRODUCT DESCRIPTION

3050 Acrylic Foam Tape is white, double-coated acrylic foam tape used in a variety of automotive applications. Considering of high performance acrylic adhesive and liner. Designed to have an excellent long term holding power. Excellent to heat resistance

APPLICATIONS

- * Interior and exterior industrial applications
- * Side molding, Emblems for automotive applications.
- * Interior and exterior automotive applications
- * Attachment of support plate for elevator.

PHYSICAL PROPERTIES

Foam	White acrylic
Adhesive	Acrylic Adhesive
Liner	Low Density Red PE film
Thickness	0.80mm(0.031 in)



TECHNICAL PERFORMANCE

Peel adhesion	1100 g/cm	
Holding power	0.5mm	23°C/min / 25mm*25mm*kg
Heat resistance	over 120°C	
Shear strength	7.0 kg/cm ²	
Tensile strength	1.0 kg/cm	
Elongation	800 %	
Density	800 kg/m ³	

WIDTH & LENGTH OF ROLL

Roll width	Roll Length
min 8mm	33 meters(36 yards)
max 800mm	66 meters(72 yards)

STORAGE DETAILS and SELF LIFE

One year from date of despatch when stored at 22°C(72°F) and 50% relative humidity. Shelf life can vary with temperature and humidity.

www.plustape.com

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore constitute a specification. Customers are strongly recommended to complete their own assessment of the product for its intended application under their own conditions/use prior to use. This documents is produced under Plustape quality procedures. Once issued, however, it is an uncontrolled documents. Please refer to conditions of sale for further information.