

# Acrylic Foam Tape

## 3060S

### PRODUCT DESCRIPTION

3060S Acrylic Foam Tape is White, double-coated acrylic foam tape used in a variety of automotive applications.

Considering of high performance acrylic adhesive and liner.  
Designed to have an excellent long term holding power.

### APPLICATIONS

- \* Interior and exterior automotive applications  
Side molding, Side visor, etc
- \* Construction bonding application: Assembly Aids, Skylight, Panel Stiffeners, Mounting Bars, Glass laminations.
- \* Transportation bonding application:  
Roof bows, FRP panels, interior panel stiffeners, Side rail bonding, etc



### PHYSICAL PROPERTIES

Foam	White Self-Stic
Adhesive	Acrylic Adhesive
Liner	Low Density Red PE film
Thickness	1.1mm(0.043 in)

### TECHNICAL PERFORMANCE

Peel adhesion	1300 g/cm	
Holding power	0.5mm	23°C/min / 25mm*25mm*kg
Heat resistance	over 100°C	
Shear strength	7.0 kg/cm <sup>2</sup>	
Tensile strength	1.2 kg/cm	
Elongation	800 %	
Density	880 kg/m <sup>3</sup>	

### WIDTH & LENGTH OF ROLL

Roll width	Roll Length
min 8mm	33 meters(36 yards)
max 800mm	66 meters(72 yards)

### STORAGE DETAILS and SELF LIFE

One year from date of despatch when stored at 22°C(72°F) and 50% relative humidity.  
Shelf life can vary with tempearture and humidity.